

PT SERIES



OJI PAPER (THAILAND)

Thermal Imaging Products

These PT series are utilized to capture bank ATM receipts for customers and ATM journal entries for banks. These items must have a high image durability, as ATM receipts must be preserved for an extended period of time. We have items for a variety of printer applications, including process control, commercial printing, and advertising.

Grade name	Substance (gsm)	Caliper (μm)	Type	FSC Mix Credit	Particularity			Sensitivity dynamic	Environmental Resistance	Image Life* Years	Application Particularity
					BPA	No BPA Added	No BPS Added				
PRINTER CD & ATM	PT 230+	72	78	●	●	☒		●●●●●	●●●●●	5	Economy CD/ATM Receipt
	PT 40065A	65	75	●	●	☒		●●●●●	●●●●●	7	Standard CD/ATM Receipt
	PT 40072A	72	78	●	●	☒		●●●●●	●●●●●	7	Standard CD/ATM Receipt
	PT 48100A	100	115	●		☒		●●●●●	●●●●●	7	Economy Receipt/Ticket
	PT 48058A	58	65	●		☒		●●●●●	●●●●●	10	Standard CD/ATM Receipt
	PT 428	65	70	●	●	☒		●●●●●	●●●●●	10	Standard CD/ATM Receipt
	PT 421	65	75	●	●	☒		●●●●●	●●●●●	12	Premium CD/ATM Receipt
	PT 48120A	120	135	●		☒		●●●●●	●●●●●	12	Standard ticket/Boarding pass
	PT 58120P	120	135	●		☒	☒	●●●●●	●●●●●	12	Standard ticket/Boarding pass

*The durability of the printed image according to our handling and storage standards.

→ Our thermal paper should be stored at a constant temperature of 23 ± 5 °C and a relative humidity of $50 \pm 10\%$.

→ Exposure to strong sunlight or strong artificial light or the influence of aggressive chemicals should be avoided.

→ Data represents product averages and does not constitute a warranty. Vender shall not be responsible for liability resulting from any deviation from this information.

→ All products should be pretested to determine suitability for any specific purpose.

→ For No BPS added, with less than 200 ppm.