

FT SERIES

Thermal Imaging Products

THERMAX
THERMAL PAPER



OJI OJI PAPER (THAILAND)

These FAX/POS series are mostly used for point-of-sale receipts at convenience stores, supermarkets, department stores, and retail stores.

In addition, we offer lineups of this series in various grammages based on customer requests.

Grade name	Substance (gsm)	Caliper (μm)	Type	FSC Mix Credit	Particularity				Sensitivity dynamic	Environmental Resistance	Image Life* Years	Application Particularity
					BPA	No BPA Added	No BPS Added	No Phenol Added				
FAX & POINT OF SALE	FT 190+	48	53	●			☒		●●●●●	●●●●●	5	Fax/POS
	FT 10055	55	62	●			☒		●●●●●	●●●●●	5	Fax/POS
	FT 210+	58	65	●	●	●	☒		●●●●●	●●●●●	5	Fax/POS
	FT 220+	65	75	●	●	●	☒		●●●●●	●●●●●	5	Fax/POS
	FT 40048A	48	53	●				☒	●●●●●	●●●●●	7	Fax/POS
	FT 40058A	58	65	●	●	●		☒	●●●●●	●●●●●	7	Fax/POS
	FT 40065A	65	75	●	●	●		☒	●●●●●	●●●●●	7	Fax/POS
	FT 330+	72	78	●	●	●		☒	●●●●●	●●●●●	7	Fax/POS
	FT 50058P	58	65	●	●	●		☒	●●●●●	●●●●●	10	Fax/POS
	FT 50065P	65	75	●	●	●		☒	●●●●●	●●●●●	10	Fax/POS

*The durability of the printed image according to our handling and storage standards.

→ Our thermal paper should be stored at a constant temperature of 23 ± 5 °C and a relative humidity of $50 \pm 10\%$.

→ Exposure to strong sunlight or strong artificial light or the influence of aggressive chemicals should be avoided.

→ Data represents product averages and does not constitute a warranty. Vendor shall not be responsible for liability resulting from any deviation from this information.

→ All products should be pretested to determine suitability for any specific purpose.

→ For No BPS added, with less than 200 ppm.