FT SERIES



Thermal Imaging Products

These FAX/POS series are mostly used for point-of-sale receipts at convenience stores, supermarkets, department stores, and retail stores. In addition, we offer lineups of this series in various grammages based on customer requests.

| | Grade | Substance | Caliper | Type | | FSC | Particularity | | | | Sensitivity | Environmental | Image Life* | Application Particularity |
|---------------------|-----------|-----------|---------|---------|-----|-----|---------------|--------------|-------------------------|-----------------|-------------|---------------|-------------|----------------------------------|
| | name | (gsm) | (µm) | Non top | Тор | CoC | BPA | No | No | No | dynamic | Resistance | Years | |
| | | | | | | | | BPA Added | BPS Added | Phenol Added | | | | |
| FAX & POINT OF SALE | FT 190+ | 48 | 53 | | | | V | | | | ••• | • • • • | 5 | Fax/POS |
| | FT 10055 | 55 | 62 | | | | V | | | | ••• | • • • • | 5 | Fax/POS |
| | FT 210+ | 58 | 65 | | | • | V | | | | ••• | • • • • | 5 | Fax/POS |
| | FT 220+ | 65 | 75 | | | • | V | | | | ••• | • • • • | 5 | Fax/POS |
| | FT 40048A | 48 | 53 | | | | | | | | ••• | • • • • | 7 | Fax/POS |
| | FT 40058A | 58 | 65 | | | • | | | | | ••• | • • • • | 7 | Fax/POS |
| | FT 40065A | 65 | 75 | | | • | | | | | ••• | • • • • | 7 | Fax/POS |
| | FT 330+ | 72 | 78 | | | • | | | | | ••• | • • • • | 7 | Fax/POS |
| | FT 50058P | 58 | 65 | | | • | | | $\overline{\mathbf{A}}$ | | ••• | • • • • | 10 | Fax/POS |
| | FT 50065P | 65 | 75 | | | • | | | V | | ••• | • • • • | 10 | Fax/POS |

^{*}The durability of the printed image according to our handling and storage standards.

- \rightarrow Our thermal paper should be stored at a constant temperature of 23 \pm 5 °C and a relative humidity of 50 \pm 10%.
- → Exposure to strong sunlight or strong artificial light or the influence of aggressive chemicals should be avoided.
- → Data represents product averages and does not constitute a warranty. Vender shall not be responsible for liability resulting from any deviation from this information.
- → All products should be pretested to determine suitability for any specific purpose.
- → For No BPS added, with less than 200 ppm.