

PT SERIES

Thermal Imaging Products



These PT series are utilized to capture bank ATM receipts for customers and ATM journal entries for banks. These items must have a high image durability, as ATM receipts must be preserved for an extended period of time. We have items for a variety of printer applications, including process control, commercial printing, and advertising.

	Grade name	Substance (gsm)	Caliper (μm)	Type		FSC CoC	Particularity				Sensitivity dynamic	Environmental Resistance	Image Life* Years	Application Particularity
				Non top	Top		BPA	No BPA Added	No BPS Added	No Phenol Added				
PRINTER CD & ATM	PT 230+	72	78	●		●	☑				● ● ● ●	● ● ● ●	5	Economy CD/ATM Receipt
	PT 40065A	65	75	●		●		☑			● ● ● ●	● ● ● ●	7	Standard CD/ATM Receipt
	PT 40072A	72	78	●		●		☑			● ● ● ●	● ● ● ●	7	Standard CD/ATM Receipt
	PT 48100A	100	115		●			☑			● ● ● ●	● ● ● ●	7	Economy Receipt/Ticket
	PT 48058A	58	65		●			☑			● ● ● ●	● ● ● ●	10	Standard CD/ATM Receipt
	PT 428	65	70		●	●		☑			● ● ● ●	● ● ● ●	10	Standard CD/ATM Receipt
	PT 421	65	75		●	●		☑			● ● ● ●	● ● ● ●	12	Premium CD/ATM Receipt
	PT 48120A	120	135		●			☑			● ● ● ●	● ● ● ●	12	Standard ticket/Boarding pass
	PT 58120P	120	135		●			☑	☑	☑	● ● ● ●	● ● ● ●	12	Standard ticket/Boarding pass

*The durability of the printed image according to our handling and storage standards.

→ Our thermal paper should be stored at a constant temperature of 23 ± 5 °C and a relative humidity of 50 ± 10%.

→ Exposure to strong sunlight or strong artificial light or the influence of aggressive chemicals should be avoided.

→ Data represents product averages and does not constitute a warranty. Vender shall not be responsible for liability resulting from any deviation from this information.

→ All products should be pretested to determine suitability for any specific purpose.

→ For No BPS added, with less than 200 ppm.